


球墨铸铁45°双盘弯管

Ductile Iron Double Flange Bend - 45°



技术参数 SPECIFICATION

- 1.测试标准/Type Test : EN14525/BS8561
- 2.橡胶标准/Elastomeric : EN681-2
- 3.球墨铸铁/Ductile Iron : EN1563 EN-GJS-450-10
- 4.涂层标准/Coating : WIS4-52-01
- 5.球墨铸铁管用附件标准/Standard : EN545/ISO2531
- 6.钻孔标准/Drilling Spec : EN1092-2

材质 MATERIALS


序号 ITEM	部件名称 PARTS	材质 MATERIAL
1	本体/Body	球墨铸铁/Ductile iron
2	密封圈/Seals	EPDM/NBR

规格DIMENSIONS(PN16)

DN	T	L	重量Mass		
			PN10	PN16	PN25
80	7	130	9.3	9.3	9.3
100	7.2	140	11.3	11.3	12.4
150	7.8	160	18.5	18.5	20.5
200	8.4	180	27.5	27	31
250	9	350	55	54	62
300	9.6	400	78	77	88
350	10.2	300	76	83	89
400	10.8	325	96	107	129
450	11.4	350	120	135	157
500	12	375	145	175	198
600	13.2	425	212	266	294
700	14.4	480	296	326	
800	15.6	530	403	442	
900	16.8	580	519	567	
1000	18	630	668	751	
1100	19.2	695	857	927	
1200	20.4	750	1050	1178	
1400	22.8	775	1412	1524	
1500	24	810	1677	1853	
1600	25.2	845	1915	2119	
1800	27.6	910	2465	2717	
2000	30	980	3149	3455	

球墨铸铁22.5°双盘弯管

Ductile Iron Double Flange Bend - 22.5°



技术参数 SPECIFICATION

- 1.测试标准/Type Test : EN14525/BS8561
- 2.橡胶标准/Elastomeric : EN681-2
- 3.球墨铸铁/Ductile Iron : EN1563 EN-GJS-450-10
- 4.涂层标准/Coating : WIS4-52-01
- 5.球墨铸铁管用附件标准/Standard : EN545/ISO2531
- 6.钻孔标准/Drilling Spec : EN1092-2

材质 MATERIALS

序号 ITEM	部件名称 PARTS	材质 MATERIAL
1	本体/Body	球墨铸铁/Ductile iron
2	密封圈/Seals	EPDM/NBR

规格DIMENSIONS(PN16)

DN	E	T	重量Mass		
			PN10	PN16	PN25
80	7	130	9.4	9.4	9.4
100	7.2	140	11.5	11.5	12.5
150	7.8	160	18.7	18.7	21
200	8.4	180	27.9	28	32
250	9	350	55.9	56	63
300	9.6	400	78.8	78.8	89
350	10.2	298	77.3	84	99.9
400	10.8	324	96.7	109	131
450	11.4	349	122	138	166
500	12	375	146	178	199.8
600	13.2	426	215.2	268	296.6
700	14.4	478	311	334	
800	15.6	529	423	453	
900	16.8	581	543	599.2	
1000	18	632	700	769	
1100	19.2	683	877	947	
1200	20.4	735	1088	1198	
1400	22.8	835	1551	1832	
1500	24	880	1838	2014	
1600	25.2	845	2180	2369	
1800	27.6	480	1640	1864	
2000	30	520	2081	2357	