

技术参数 SPECIFICATION


- 1. 测试标准/Type Test : EN14525/BS8561
- 2. 橡胶标准/Elastomeric : EN681-2
- 3. 球墨铸铁/Ductile Iron : EN1563 EN-GJS-450-10
- 4. 涂层标准/Coating : WIS4-52-01
- 5. 球墨铸铁管用管件标准/Standard : EN545/ISO2531
- 6. 钻孔标准/Drilling Spec : EN1092-2

材质 MATERIALS

序号 ITEM	部件名称 PARTS	材质 MATERIAL
1	本体/Body	球墨铸铁/Ductile iron

规格DIMENSIONS(PN16)

DN×dn	T	L	t	H	重量Mass		
					PN10	PN16	PN25
80×80	7	330	7	165	15.6	15.6	15.6
100×80	7.2	360	7	175	18.4	18.4	19.5
100×100	7.2	360	7.2	180	19.4	19.4	21
150×80	7.8	440	7	205	28.5	28.5	31
150×100	7.8	440	7.5	210	29.5	29.5	32
150×150	7.8	440	7.8	220	32.5	32.5	36
200×80	8.4	520	7	235	42	41.5	46
200×100	8.4	520	7.2	240	43	42	47.5
200×150	8.4	520	7.8	250	46	45.5	51
200×200	8.4	520	8.4	260	49.5	49	56
250×80	9	700	7	270	49.7	49.3	56.7
250×100	9	700	7.2	275	68	67	75
250×150	9	700	7.8	300	73.5	71	81
250×200	9	700	8.74	325	76	75	85
250×250	9	700	9	350	82	81	93
300×100	9.6	800	7.2	300	94	93	105
300×150	9.6	800	7.8	325	99	98.5	100
300×200	9.6	800	8.4	350	102	101	114
300×250	9.6	800	9	375	109	108	121
300×300	9.6	800	9.6	400	116	115	131
350×100	10.2	850	7.2	325	116	122	139
350×150	10.2	850	7.8	325	120	126	143
350×200	10.2	850	8.4	325	121	128	148
350×250	10.2	850	9	325	128	134	154
350×300	10.2	850	9.6	425	140	145	166
350×350	10.2	850	10.2	425	142	151	176
400×100	10.8	900	7.2	350	143	164	177
400×150	10.8	900	7.8	350	144	158	181
400×200	10.8	900	8.4	350	148	159	184
400×250	10.8	900	9	350	151	161	196
400×300	10.8	900	9.6	400	168	177	204
400×350	10.8	900	10.2	450	170	183	215
400×400	10.8	900	10.8	450	174	191	225



技术参数 SPECIFICATION

- 1. 测试标准/Type Test : EN14525/BS8561
- 2. 球墨铸铁/Ductile Iron : EN1563 EN-GJS-450-10
- 3. 涂层标准/Coating : WIS4-52-01
- 4. 球墨铸铁管用管件标准/Standard : EN545/ISO2531
- 5. 钻孔标准/Drilling Spec : EN1092-2

材质 MATERIALS

序号 ITEM	部件名称 PARTS	材质 MATERIAL
1	本体/Body	球墨铸铁/Ductile iron

规格DIMENSIONS(PN16)

DN×dn	T	t	L	重量Mass		
				PN10	PN16	PN25
100×80	7.2	7	200	9.3	9.3	9.3
150×80	7.8	7	400	16.4	16.4	17.4
150×100	7.8	7.2	300	15.3	15.3	16.8
200×100	8.4	7.2	600	27.5	27.5	30
200×150	8.4	7.8	300	22	21.5	31.5
250×150	9	7.8	600	39	39	43.5
250×200	9	8.4	300	30	29.5	35.5
300×150	9.6	7.8	650	48.5	48.5	55
300×200	9.6	8.4	600	52	51.5	59
300×250	9.6	9	300	40.5	39.5	49
350×200	10.2	8.4	650	61.5	64	74
350×250	10.2	9	600	65.5	67.5	79
350×300	10.2	9.6	300	49.5	52.5	66
400×200	10.8	8.4	700	73.5	77.5	90.5
400×250	10.8	9	650	77	81.5	96
400×300	10.8	9.6	600	80.5	85	101
400×350	10.8	10.2	300	58	67	86
450×250	11.4	9	700	89.5	97	112
450×300	11.4	9.6	650	93.5	101	117
450×350	11.4	10.2	600	95.6	106	126
450×400	11.4	10.8	300	70.5	83	105
500×300	12	9.6	700	109	122	138
500×350	12	10.2	650	111	127	145
500×400	12	10.8	600	110	130	153
500×450	12	11.4	300	83	104	126
600×350	13.2	10.2	750	147	174	193
600×400	13.2	10.8	700	150	178	201